

Cs12 LPS1175 Security Level 2 Retractable Security Grille







Key Benefits

- Commercial and Retail
- Retractable Security Grille
- Internally Fixed
- Tested by the LPCB to LPS1175 Security Level 2
- Secured By Design
- Aluminium construction
- 2 Point Locking System
- "X" Lattice Design
- Powder Coated White as standard
- 4-6 week lead time (Subject to change)

Secured by Design



Police Preferred Specification



Product Overview

Description

The CS12 is a High Security Insurance Approved Retractable Security Grille for Windows and Doors. Independently Tested by the LPCB to LPS1175 Security Rating Level 2. This is a Secured By Design product, which is a Police and Insurance preferred specification. The CS12 comes as standard with a Two Point Hook Lock built into the grille and Lock protection plates for added strength and security. The grille is Top Rolling for smooth operation and is available with the "X" Lattice design. Fitted Internally, it can be Single Stack as standard or Double Stack at an extra cost. The grille is available with Lift Up Bottom Tracks for Doorways.

Common use

Fitted internally to provide security to doors and windows.

Maximum Width

6000mm

Maximum Height

2700mm

Weight

19kgs m/2

Standard Finish

Powder Coated White RAL9016 as standard. Other BS and RAL Colours available at an extra cost.

Lead Time

20-30 working days (subject to change)



Specification

The following lists the preferred terminology applied to gates (in Bold) and alternatives which are also in common use:

SASH – Bunch / Stack / Hand

TOP TRACK – Top runner / Top Rail / Top Guide

FOLDING TRACK – Lift up / Hinge (should not be used -can be confused with the hinge aside option)

REMOVABLE TRACK – Lift Out / Lift Off


HINGE ASIDE – Hinging Sash / Swinging Sash / Fold Back

C-SIDE FIXING FRAME - C-Side / Reinforcing for Top Track / Strengthening for Top Track

REVEAL FIXED – Between Walls / Recess
 FACE FIXED – Surface Mounted / Plant On
 BI-PARTING – Double / Double Draw / Split

KEYED ALIKE – Suited / Same

PICKET – Upright





Specification

Lattice

The Cs12 is only available with "X" Lattice Design.



Locking

The Cs12 has a two point Multi Point Locking system, with attack plates built into the locking post..




Top and Bottom Tracks

The Cs12 has Extruded Aluminium top and bottom tracks. *Please see fixing details*.



Bottom Track



Top Track




Specification

Stacking Options

Bunch Sizes mm				
	SINGLE SASH		DOUBLE SASH	
OVERALL GATE	SINGLE	CLEAR OPENING	DOUBLE SASH PER	CLEAR OPENING
WIDTH 'A'	BUNCH	WIDTH 'C'	BUNCH	WIDTH 'E'
mm	"B"	mm	'D'	mm
			"""	
500 600	135 135	315 415	 	
700	150	500		
800	165	585		
900	180	670		
1000	180	770	135	730
1100	195	855	135	830
1200	210	940	150	900
1300	225	1025	150	1000
1400	225	1125	150	1100
1500	240	1210	165	1170
1600	255	1295	165	1270
1700	270	1380	180	1340
1800	285	1465	180	1440
1900	285	1565	180	1540
2000	300	1650	195	1610
2100	315	1735	195	1710
2200	330	1820	195	1810
2300	330	1920	210	1880
2400	345	2005	210	1980
2500	360	2090	225	2050
2600	375	2175	225	2150
2700 2800	375 390	2275 2360	225 240	2250 2320
2900	405	2445	240	2420
3000	403	2530	255	2420
3100	435	2615	255	2590
3200	435	2715	255	2690
3300	450	2800	270	2760
3400	465	2885	270	2860
3500	480	2970	270	2960
3600	480	3070	285	3030
3700	495	3155	285	3130
3800	510	3240	300	3200
3900	525	3325	300	3300
4000	525	3425	300	3400
4100	540	3510	315	3470
4200	555	3595	315	3570
4300	570	3680	330	3640
4400	585	3765	330	3740
4500	585	3865	330	3840
4600	600	3950	345	3910
4700	615	4035	345	4010
4800	630 630	4120 4220	345	4110 4180
4900 5000	645	4220	360 360	4180
5100	660	4303	375	4350
5200	675	4475	375	4450
5300	675	4575	375	4550
5400	690	4660	390	4620
5500	705	4745	390	4720
5600	720	4830	405	4790
5700	735	4915	405	4890
5800	735	5015	405	4990
5900	750	5100	420	5060
6000	765	5185	420	5160

Please note: The clear opening widths detailed above apply to retractable gates with fixed tracks. If the gate requires folding bottom tracks or the hinge aside option (with or without folding bottom tracks) you will need to add 60mm per bunch to the bunch sizes above.


^{*}Please ask for details on widths greater than 6m





Specification


Reveal Fixing Detail - Solid Walls







Specification

Reveal Fixing Detail - Dry Line Walls









Colours

