

Security Direct property protection Large Product Range Competitive Prices 25 years Experience

## Cs13 - Eclipse LPS1175 Security Level 3 Retractable Security Grille







### **Key Benefits**

- Commercial and Retail
- Retractable Security Grille
- Internally Fixed
- Tested by the LPCB to LPS1175 Security Level 3
- Secured By Design
- Aluminium construction
- 2 Point Locking System
- "X" Lattice Design
- Powder Coated White as standard
- 4-6 week lead time (Subject to change)



www.securitydirectuk.com





### **Product Overview**

#### Description

The CS13 is a High Security Insurance Approved Retractable Security Grille for Windows and Doors. Independently Tested by the LPCB to LPS1175 Security Rating Level 2. This is a Secured By Design product, which is a Police and Insurance preferred specification. The CS13 comes as standard with a Two Point Hook Lock built into the grille and Lock protection plates for added strength and security. The grille is Top Rolling for smooth operation and is available with the "X" Lattice design. Fitted Internally, it can be Single Stack as standard or Double Stack at an extra cost. The grille is available with Lift Up Bottom Tracks for Doorways.

Common use

Fitted internally to provide security to doors and windows.

Maximum Width 6000mm

Maximum Height 2700mm

Weight 19kgs m/2

#### Standard Finish

Powder Coated White RAL9016 as standard. Other BS and RAL Colours available at an extra cost.

#### Lead Time


20-30 working days (subject to change)



## **Specification**

The following lists the preferred terminology applied to gates (in Bold) and alternatives which are also in common use:

SASH	– Bunch / Stack / Hand			
TOP TRACK	– Top runner / Top Rail / Top Guide			
FOLDING TRACK	- Lift up / Hinge (should not be used -can be confused with the hinge aside option)			
<b>REMOVABLE TRACK</b>	<ul> <li>Lift Out / Lift Off</li> </ul>			
HINGE ASIDE	– Hinging Sash / Swinging Sash / Fold Back			
C-SIDE FIXING FRAME	<ul> <li>C-Side / Reinforcing for Top Track / Strengthening for Top Track</li> </ul>			
REVEAL FIXED	– Between Walls / Recess			
FACE FIXED	– Surface Mounted / Plant On			
<b>BI-PARTING</b>	– Double / Double Draw / Split			
KEYED ALIKE	– Suited / Same			
PICKET	– Upright			





## **Specification**

#### Lattice

The Cs13 is only available with "X" Lattice Design.




#### Locking

The Cs13 has a two point Multi Point Locking system, with attack plates built into the locking post..




### **Top and Bottom Tracks**

The Cs13 has Extruded Aluminium top and bottom tracks. *Please see fixing details.* 



**Bottom Track** 



**Top Track** 




### **Specification**

#### **Stacking Options**

Bunch Sizes mm						
0.00	SINGLE			E SASH		
OVERALL GATE	SINGLE SASH	CLEAR OPENING	DOUBLE SASH PER	CLEAR OPENING		
WIDTH	BUNCH	WIDTH	BUNCH	WIDTH		
'A'	'B'	'C'	'D'	WIDTH 'E'		
mm	mm	mm	mm	mm		
500	135	315				
600	135	415				
700	150	500				
800	165	585				
900	180	670				
1000	180	770	135	730		
1100	195	855	135	830		
1200	210	940	150	900		
1300	225	1025	150	1000		
1400	225	1125	150	1100		
1500	240	1210	165	1170		
1600	255	1295	165	1270		
1700	270	1380	180	1340		
1800	285	1465	180	1440		
1900	285	1465	180	1540		
2000	300	1650	195	1610		
2000	315	1735	195	1710		
2200	330	1820	195	1810		
2300	330	1920	210	1880		
2400	345	2005	210	1980		
2500	360	2090	225	2050		
2600	375	2175	225	2150		
2700	375	2275	225	2250		
2800	390	2360	240	2320		
2900	405	2445	240	2420		
3000	420	2530	255	2490		
3100	435	2615	255	2590		
3200	435	2715	255	2690		
3300	450	2800	270	2760		
3400	465	2885	270	2860		
3500	480	2970	270	2960		
3600	480	3070	285	3030		
3700	495	3155	285	3130		
3800	510	3240	300	3200		
3900	525	3325	300	3300		
4000	525	3425	300	3400		
4100	540	3510	315	3470		
4200	555	3595	315	3570		
4300	570	3680	330	3640		
4400	585	3765	330	3740		
4500	585	3865	330	3840		
4600	600	3950	345	3910		
4700	615	4035	345	4010		
4800	630	4120	345	4110		
4900	630	4220	360	4180		
5000	645	4305	360	4280		
5100	660	4390	375	4350		
5200	675	4475	375	4450		
5300	675	4575	375	4550		
5400	690	4660	390	4620		
5500	705	4745	390	4720		
5600	720	4830	405	4790		
5700	735	4915	405	4890		
5800	735	5015	405	4990		
5900	750	5100	420	5060		
6000	765	5185	420	5160		


Please note: The clear opening widths detailed above apply to retractable gates with fixed tracks. If the gate requires folding bottom tracks or the hinge aside option (with or without folding bottom tracks) you will need to add 60mm per bunch to the bunch sizes above.

\*Please ask for details on widths greater than 6m



Note: Folding tracks with a length of 600mm or more are supplied with a retaining pin as standard. This is located between 488mm and 568mm from the ground regardless of track length. The retaining pin projects 60mm beyond the lock post when the

track is lowered and 30mm when raised. If the width of the gate is greater than the height check that there will be sufficient room for the bottom track to fold up into.




Uneven Sashes On double sash gates, the sashes can be split with the majority opening to one side, useful where there is a preference or a limited space at one side of the aperture to accommodate the retracted sash.



## **Specification**

### **Reveal Fixing Detail - Solid Walls**




www.securitydirectuk.com



### **Specification**

#### Reveal Fixing Detail - Dry Line Walls



#### www.securitydirectuk.com



### Colours

