



Security Direct
property protection

- Large Product Range
- Competitive Prices
- 25 years Experience

Child Safety Window Barrier



SECURITYDIRECT
Specialist Security Solutions

Child Safety Window Barrier



Key Benefits

- Residential, Nurseries, Schools, Sports Centres
- Fixed Safety Window Barrier
- Internally Fixed
- Medium Security
- All Steel construction
- 12mm Infill Bars
- Fixed and Removable options
- Powder Coated One of 50 Standard colours
- 2-3 week lead time (Subject to change)

Child Safety Window Barrier



Product Overview

Description

The Child Safety Barrier has been specially designed for preventing children from falling from low windows. The barrier is fitted internally, across the front of the window or with the window recess. The vertical bars are closer together, to ensure children can't get their head stuck between the bars. The barrier can be made to suit to fit a half height window or full height window. The barrier can be made fixed for more security or removable, to allow the grille to be removed for cleaning the window and maintenance.

The child safety window barrier has been designed to comply with the guidance specified in Part K2 of the Building Regulations 2000 as read with BS6180:1999. As an added precaution the spacing between the bars has also been reduced in order to comply with that specified in BSEN 1930:2000.

Common use

Fitted internally over windows.

Maximum Width

2500mm

Maximum Height

2500mm

Weight

20kgs m/2

Standard Finish

Powder Coated one of 50 standard colours.

Lead Time

10-15 working days (subject to change)

Child Safety Window Barrier



Specification

Infill

The Safety Barrier is manufactured using 12mm Round Vertical Bars welded into a steel Frame. To prevent children trapping their head in between the bars, the bars are spaced at 65mm.



Child Safety Window Barrier




Specification


Frame

The Window Bars come as standard with a Box Section frame, other types of frame are available on request.


BOX SECTION - The Bar grille is supplied as standard in a fully welded Box Section frame. The size of the box section will depend on the Diameter of the infill bars. The bars are welded into the frame, providing a very strong bar grille. The advantage of the box section is that the fixings can be concealed inside the box section profile, making it a neater and more secure than the other frame types.



FLAT BAR FRAME - the vertical bars are welded into a full frame which is manufactured from Flat Steel Bar. The flat bar frame is ideal when face fixing onto a wall or back of a door.



ANGLE FRAME - the vertical bars are welded into a full frame which is made from Angle Iron. Angle frame is often used in warehouses, where aesthetics are not important.



Child Safety Window Barrier




Specification

Options


FIXED - The Bar grille is supplied as standard as a Fixed Panel. On larger sizes the grille maybe supplied in sections and required bolting together on site.

FIXED




Hinged - There is the option of having the Bar Grille as a Hinged Gate. Ideal for emergency escape, where access is required or for maintenance and cleaning.

HINGED



Lit Out - There is the option of having the grille lift out and lockable if required. This is only available on small openings.


LIFT OUT






Specification

Standard Reveal Fixing




Plan View

Standard Face Fixing



Plan View

Optional Stand Off Fixing



Plan View

Child Safety Window Barrier



Colours

STANDARD COLOURS



BAND A COLOURS



BAND B COLOURS



BAND C COLOURS



Please note the colours illustrated will not be an exact match and are intended as a guide only