IR4 DATA SHEET

TIMIDATOR HIGH PERFORMANCE INDUSTRIAL DOORS

A1 (SR1) B3 (SR2) C5 (SR3) D10 (SR4) LPS 1175 CERTIFIED INDUSTRIAL DOORS







ACCREDITATIONS

- Independently tested by the Loss Prevention • Certification Board (LPCB)
- Certified to LPS 1175 Issue 8, D10 (SR4)
- Secured by Design Police Preferred Specification

TYPICAL APPLICATIONS

- High risk commercial buildings
- Government & Defence
- **Critical Infrastructure**
- Laboratories





OPTIONS

- Galvanised steel or stainless steel curtain construction
- Polyester powder coat to any standard RAL / • BS colour
- Manual or auto locking .
- High or standard duty cycle motors
- Thermal insulation upgrade
- Acoustic insulation upgrade •







Version 1.0

Asse, to ISO 9001; 2015 Cert/LPCB ref. 1396

IR4 DATA SHEET

A1 (SR1)

B3 (SR2) C5 (SR3)

D10 (SR4)

LPS 1175 CERTIFIED INDUSTRIAL DOORS

TIMIDATOR

HIGH PERFORMANCE INDUSTRIAL DOORS

PRODUCT REFERENCE

• Intimidator IR4 Industrial Door

APPROVED DIMENSIONS

- Maximum width:
 8000mm
 - Maximum height:
 8000mm
- Minimum width: 1750mm
- Minimum height: 1000mm

SHUTTER CURTAIN

- Double Wall Stainless Steel
- Double Wall Galvanised Steel

FRAMES/GUIDES

• Two-part galvanised steel guide with rubber seals





SUBSTRATE

- Reinforced masonry
- Reinforced concrete
- Structural Steelwork
- Sub assembly steel framework

OPERATION

- Hold-to-run operation with manual locks
- Automatic operation with electronic locks
- Safety on close as assessment directs

BOTTOM RAIL

- Reinforced steel
- Weather seal

Distributor

Intimidator Doors are manufactured in the UK by CGT Security Ltd