

Security Direct property protection

Large Product Range Competitive Prices 25 years Experience

Ra9 Aluminium Grille Roller Shutter







Key Benefits

- Commercial, Retail, Bars and Serveries
- Ideal for wider openings up to 5m
- Aluminium Grille Curtain 69% Vision
- Medium Security
- Aluminium
- Manual and Electric Operation
- Smaller spacing available for added security
- Curtain Anodised Silver
- 2 week lead time (Subject to change)

www.securitydirectuk.com



Product Overview

Description

The RA9 Aluminium Roller Grille is a modern version of the old fashioned Tube & Link style shutter. The RA9 provides the same amount of vision, provides a higher level of security and is a lot more cost effective than the Tube & Link Shutters. The RA9 Aluminium Roller is only suitable for Internal use. The RA9 comes with a standard spacing of 150mm x 70mm. For added security and preventing hand getting through the curtain, there is the option of a closer spacing of 75mm x 70mm.

Common use

Commercial, Retail, Bars and Serveries

Maximum Width (*Depending on Height*) 5000mm

Maximum Height (Depending on Width) Manual - 2800mm Electric - 4000mm

Weight 7kgs m/2

Standard Finish

Curtain - Anodised Silver Box & Guides - White, Brown, Cream, Black

Lead Time


10 working days (subject to change)

Specification

LATH SPECIFICATION

Laths

The Ra9 Curtain is a Anodised Silver Grille. With 150mm w x 70m h spacing, providing up 69% vision. The Laths can be "In-Line" as standard or "Brickbond" at no additional cost. 75mm smaller spacing is available at an extra cost.



www.securitydirectuk.com



Specification

BOX SPECIFICATION

Die cast Aluminium end plates with two piece roll formed Aluminium casing


Box Sizes

Overall Shutter height (including shutter box) - (May change to on larger widths)

1600 mm - 205mm box


2800 mm - 250 mm box

4000 mm - 300 mm box



GUIDE RAIL SPECIFICATION

As standard the Ra9 comes with the Extruded Aluminium Guides with an integral box section for reinforcement and to facilitate fixing.





Operation

The RA9 is available both manually and electrically operated using a tubular motor inside the barrel. The options priced are shown on your quotation which also shows the method of operation we have included. This list shows possible options which would incur different costs.

SPRING LOADED

Roller Shutters usually installed mainly over doorways or Serveries are raised up and down by lifting and lowering the curtain by hand. The roller shutter has a spring in the barrel which helps lifting the shutter. As standard a central bottom lath lock is provided which has a key in the bottom lath and bolts shoot into the guides rails at each side. The Bottom lath lock can be operated from both sides but has a secure and non-secure side to the lock. Optional bullet locks are available which are pins that go through the guide rails each side.

ELECTRIC - (N.B. minimum shutter width 755mm)

Electric shutters are usually fitted on larger openings where Manual Operation is not suitable or where the operator requires an easy, clean and user friendly type of operation. Single phase tubular motors are enclosed within the barrel giving full protection from the elements. Electric Roller Shutters can be controlled individually or grouped to one controller. The controllers available include internal rocker switch, security key switch or Remote Control. Manual overrides are available on Electric Roller Shutters which allow the shutter to be operated when the power to the shutter has failed.



Colours



Please note the colours illustrated will not be an exact match and are intended as a guide only

STANDARD COLOURS

www.securitydirectuk.com