

964 PRODUCT DATA SHEET

SR2

SR3

SR4



ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 7, Security Rating 4 (SR4)
- Secured by Design Police Preferred Specification



SELF-LOCKING TECHNOLOGY

- No auxiliary locking required - manual or electronic
- Unique profiles lock the shutter in any stop position - fully closed or not
- Allows external first point of entry through the shutter



TYPICAL APPLICATIONS

Suitable applications include:

- Laboratories, Research and Data Storage Facilities
- Critical National Infrastructure
- Cash and Valuables in Transit
- Government and Defense



OPTIONS

- Polyester powder coated to any standard RAL /BS colour
- High or low duty cycle electrical motors
- Internal and External installations complete with sub assembly steel frames as required
- Variable reinforced core to protect against specific attack methodology



SECURITY DIRECT
www.securitydirectuk.com

964 PRODUCT DATA SHEET

SR2

SR3

SR4

PRODUCT REFERENCE

Xonar 964 Security Shutter

Certified to LPS 1175, Issue 7, Security Rating 4 (SR4)

APPROVED DIMENSIONS

External Face Fit

Maximum certified width: 6.0m

Minimum certified width: 1.0m

Maximum certified height: 6.0m

Minimum certified height: 1.8m

Internal Face Fit

Maximum certified width: 6.0m

Minimum certified width: 1.0m

Maximum certified height: 6.0m

Minimum certified height: 1.0m

SHUTTER CURTAIN

Extruded aluminium self-locking profiles with reinforced cores.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

BOTTOM RAIL

Reinforced extruded aluminium section with strengthened core.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

FRAMES/GUIDES

Heavy duty extruded aluminium guide profiles anchored direct to the structure.

Finish as delivered: polyester powder coated in standard RAL/BS colour.



SUBSTRATE

Certified installation onto:

Blockwork

Concrete

Structural Steelwork

Sub assembly steel framework

OPERATION

Motorised to allow controlled ascent and descent.

Tube Motor - Low duty cycle, or where limited to single phase supply.

External Drive Motor - High duty cycle or for larger apertures.

CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or possible to integrate into building management systems and third party alarms.

Safety on close as assessment directs.

High duty cycle motor and battery backup options.



SECURITY DIRECT
www.securitydirectuk.com