

IR3 DATA SHEET

INTIMIDATOR

HIGH PERFORMANCE INDUSTRIAL DOORS



A1 (SR1)

B3 (SR2)

C5 (SR3)

D10 (SR4)

LPS 1175 CERTIFIED INDUSTRIAL DOORS



ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 8, C5 (SR3)
- Secured by Design Police Preferred Specification



TYPICAL APPLICATIONS

- High value commercial buildings
- Utilities Buildings
- High value storage
- Data centres



OPTIONS

- Aluminium, galvanised steel or stainless steel shutter curtain construction
- Single skin steel curtain construction
- Polyester powder coated to any standard RAL/BS colour
- Manual or auto locking
- High or standard duty cycle motors
- Thermal insulation upgrade
- Acoustic insulation upgrade

IR3 DATA SHEET

INTIMIDATOR

HIGH PERFORMANCE INDUSTRIAL DOORS

A1 (SR1)

B3 (SR2)

C5 (SR3)

D10 (SR4)

LPS 1175 CERTIFIED INDUSTRIAL DOORS

PRODUCT REFERENCE

- Intimidator IR3 Industrial Door

APPROVED DIMENSIONS

- | | |
|----------------------------|-----------------------------|
| • Maximum width:
8000mm | • Maximum height:
8000mm |
| • Minimum width:
1000mm | • Minimum height:
1000mm |



SHUTTER CURTAIN OPTIONS

- Single Wall Galvanised Steel
- Double Wall Aluminium
- Double Wall Galvanised Steel
- Double Wall Stainless Steel

FRAMES/GUIDES

- Two-part galvanised steel guide with rubber seals



SUBSTRATE

- Brickwork
- Blockwork
- Concrete
- Structural Steelwork
- Sub assembly steel framework

OPERATION

- Hold-to-run operation with manual locks
- Automatic operation with electronic locks
- Safety on close as assessment directs

BOTTOM RAIL

- Reinforced steel
- Weather seal

Distributor

